















EXACT T-Grip cordless screwdrivers



T-Grip Features

- ▶ Precision Shut-off clutch exceeds ISO tolerance of $\pm 10\%$
- ▶ Lightweight
- ▶ Broad torque range
- ▶ 0.7 sec. trigger repeat protection
- ▶ LED/audible battery charge indicators disable tool when voltage drops below threshold; tool stays “in-process” regardless of battery condition
- ▶ LED/audible shut-off indicator provides operator feedback for clutch signal to confirm good/bad joint status (sent via Bluetooth to controller on BT-EXACT models)
- ▶ Bright LED light for work area illumination
- ▶ All models feature trigger hand forward/reverse control
- ▶ Tools share many common parts
- ▶ Color rings are used to identify joint types on the assembly line
- ▶ Protective rubber cover available for quick-change bit holder
- ▶ Tool holding fixtures available
- ▶ Batteries available with tool, individually or as a 10-pack
- ▶ All models can be hung from balancer using accessory hook (part # 3 601 923 024)
- ▶ Bluetooth models require wireless EXAConnect controller (sold separately)

EXACT		Tool order number	Torque on hard joint per ISO 5393	Torque on soft joint per ISO 5393
EXACT 2 fine torque adjustment		0 602 490 450	0.6 – 2Nm 0.4 – 1.5 ft/lbs	0.6 – 2Nm 0.4 – 1.5 ft/lbs
		0 602 490 460		
BT-EXACT 2 Bluetooth enabled		0 602 491 434	5.3 – 17.7 in/lbs	5.3 – 17.7 in/lbs
		0 602 491 433		
EXACT 4 high speed		0 602 490 451	0.6 – 4Nm 0.4 – 3 ft/lbs	0.6 – 4Nm 0.4 – 3 ft/lbs
		0 602 490 461		
BT-EXACT 4 Bluetooth enabled		0 602 491 438	5.3 – 35.4 in/lbs	5.3 – 35.4 in/lbs
		0 602 491 437		
EXACT 6 good torque & speed		0 602 490 452	1 – 6Nm 0.7 – 4.4 ft/lbs	1 – 6Nm 0.7 – 4.4 ft/lbs
		0 602 490 462		
BT-EXACT 6 Bluetooth enabled		0 602 491 432	8.8 – 53 in/lbs	8.8 – 53 in/lbs
		0 602 491 431		
EXACT 7 great for hose clamps		0 602 490 454	1 – 7Nm 0.7 – 5.2 ft/lbs	1 – 7Nm 0.7 – 5.2 ft/lbs
		0 602 490 464		
BT-EXACT 7 Bluetooth enabled		0 602 491 440	8.8 – 62 in/lbs	8.8 – 62 in/lbs
		0 602 491 439		
EXACT 9 high torque/low weight		0 602 490 453	1 – 9Nm 0.7 – 6.7 ft/lbs	1 – 9Nm 0.7 – 6.7 ft/lbs
		0 602 490 463		
BT-EXACT 9 Bluetooth enabled		0 602 491 436	8.8 – 79.6 in/lbs	8.8 – 79.6 in/lbs
		0 602 491 435		
EXACT 8 good torque & speed		0 602 490 456	1.5 – 8Nm 1.1 – 5.9 ft/lbs	1.5 – 8Nm 1.1 – 5.9 ft/lbs
		0 602 490 466		
BT-EXACT 8 Bluetooth enabled		0 602 491 444	13 – 70.8 in/lbs	13 – 70.8 in/lbs
		0 602 491 443		
EXACT 12 high torque		0 602 490 457	1.5 – 12Nm 1.1 – 9 ft/lbs	1.5 – 12Nm 1.1 – 9 ft/lbs
		0 602 490 467		
BT-EXACT 12 Bluetooth enabled		0 602 491 442	13.3 – 106 in/lbs	13.3 – 106 in/lbs
		0 602 491 441		

No-load speed (rpm)	Bit holder	Battery specifications refer to page 26	Direction of rotation R = right L = left	Weight kg/lbs	Features	Included accessories	Accessory part number
600	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 sec. repeat protection	Torque adjustment tool light green color ring	3 607 950 020 3 600 106 008
600	1/4" QC	Not included	R/L	0.8 / 1.76	0.7 sec. repeat protection		
600	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	Class 2 Bluetooth module		
600	1/4" QC	Not included	R/L	0.8 / 1.76	Class 2 Bluetooth module		
900	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 sec. repeat protection	Torque adjustment tool grey color ring	3 607 950 020 3 600 106 016
900	1/4" QC	Not included	R/L	0.8 / 1.76	0.7 sec. repeat protection		
900	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	Class 2 Bluetooth module		
900	1/4" QC	Not included	R/L	0.8 / 1.76	Class 2 Bluetooth module		
600	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 sec. repeat protection	Torque adjustment tool black color ring	3 607 950 020 3 600 106 005
600	1/4" QC	Not included	R/L	0.8 / 1.76	0.7 sec. repeat protection		
600	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	Class 2 Bluetooth module		
600	1/4" QC	Not included	R/L	0.8 / 1.76	Class 2 Bluetooth module		
150	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 sec. repeat protection	Torque adjustment tool white color ring	3 607 950 020 3 600 106 018
150	1/4" QC	Not included	R/L	0.8 / 1.76	0.7 sec. repeat protection		
150	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	Class 2 Bluetooth module		
150	1/4" QC	Not included	R/L	0.8 / 1.76	Class 2 Bluetooth module		
350	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 sec. repeat protection	Torque adjustment tool light blue color ring	3 607 950 020 3 600 106 007
350	1/4" QC	Not included	R/L	0.8 / 1.76	0.7 sec. repeat protection		
350	1/4" QC	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	Class 2 Bluetooth module		
350	1/4" QC	Not included	R/L	0.8 / 1.76	Class 2 Bluetooth module		
650	1/4" QC	12 V / 2.4 Ah	R/L	1.6 / 3.5	0.7 sec. repeat protection	Torque adjustment tool orange color ring	3 607 950 020 3 600 106 009
650	1/4" QC	Not included	R/L	0.9 / 2.0	0.7 sec. repeat protection		
650	1/4" QC	12 V / 2.4 Ah	R/L	1.6 / 3.5	Class 2 Bluetooth module		
650	1/4" QC	Not included	R/L	0.9 / 2.0	Class 2 Bluetooth module		
400	1/4" QC	12 V / 2.4 Ah	R/L	1.6 / 3.5	0.7 sec. repeat protection	Torque adjustment tool red color ring	3 607 950 020 3 600 106 006
400	1/4" QC	Not included	R/L	0.9 / 2.0	0.7 sec. repeat protection		
400	1/4" QC	12 V / 2.4 Ah	R/L	1.6 / 3.5	Class 2 Bluetooth module		
400	1/4" QC	Not included	R/L	0.9 / 2.0	Class 2 Bluetooth module		